

LOMON® R-996

Titanium Dioxide Pigment

PRODUCT DESCRIPTION

LOMON® R-996 is Zirconia and Alumina treated rutile titanium dioxide pigment. It is proved to have excellent outdoor durability and super gloss in paint & coating, ink and plastic industries.

APPLICATIONS

LOMON® R-996 is recommended as a premium pigment for a variety of high quality powder coatings, water-born and solvent-born industrial and decorative coating, ink and plastics.

TECHNICAL DATA SHEET

TYPE	R-996		
Crystal Form	Rutile		
Classification ISO591, DIN55912	R2		
ASTM D476			
CAS No.	13463-67-7		
TiO2 Content(%) min	93		
pH Value	6.5~8.5		
Density(g/cm ³)	4.0		
Oil Absorption (g/100g) max	22		
Specific Resistance(Ω m) min	150		
Average Particle Size(µ m)	0.23		
Surface Treatment	Zirconia & Alumina, Organic		

- The information in this publication is, to be best of our knowledge, true but since the conditions of use are beyond our control, the values provided are not to be considered as a warranty or to be implied in respect of such information.
- In every case caution must be exercised to avoid violation or infringement of statutory obligations and any rights belonging to a third party.
- We are, at all times, willing to study customer specific outlets involving our products in order to enable their most effective use.

Av. Los Bucares, Prado de María, Caracas, Venezuela.

Telf: +58-212-632.02.25 / 3686

Email: contacto@vitrofibras.com Web: www.vitrofibras.com





COMPARABLE PRODUCT TEST REPORT

COATING SOLUTIONS:

Alkyd Melamine Enamel Test:

Binder 32% coconut alkyd / butylated melamine=70/30 (solid)

Grinding Red Devil 5400 Paint Conditioner
Enamel Dry PVC 24%, Pig / Binder solid=1.2

Coating For Gloss and Color evaluation, coated with 150 micron wet thick

applicator on a glassplate and baked for 20 minutes at 130 degree

Centigrade.

For Opacity evaluation, coated with 60 micron wet thick Barcoater on

a black and white paper.

	R-996	Competitive A	Competitive B	Competitive C
Fineness of grinding	(µ m)	(µ m)	(µ m)	(µ m)
For 3 min	17	20	17	15
9 min	14	17	13	12
15min	12	16	12	10
21min	10	15	10	8
40min	<5	12	<5	<5
60 Specular Gloss	89	87	89	90
Color	- 4	2. (11)	10	
L	93.9	93.7	94.0	94.0
a	-1.0	-0.9	-0.9	-1.0
b	0.6	1.2	0.8	0.9
Whiteness	93.8	93.5	93.9	93.8
Opacity				
Y on black substrate	75.6	74.7	75.8	75.7
Y on white substrate	84.7	83.9	84.8	84.5
Contrast Ratio	89.3	89.1	89.4	89.6

For information only

Not for regulatory purposes

SAFETY & HEALTH INSTRUCTION

All Lomon TiO2 products including R996 are not hazardous article according to international standard. Material Safety Data Sheet will be provided.

PACKING & TRANSPORTION

25KG, 500KG and 1000KG, seaworthy and suitable for container transportation

Av. Los Bucares, Prado de María, Caracas, Venezuela.

Telf: +58-212-632.02.25 / 3686

Email: contacto@vitrofibras.com Web: www.vitrofibras.com